ANNTOINETTE TIDE





ALUCAT 2206 FAST CREWBOAT

Vessel Characteristics

Length, Overall:	72.5 ft	22.1 m
Beam:	18.7 ft	5.7 m
Depth:	8.2 ft	2.5 m
Maximum Draft:	3.9 ft	1.2 m
Minimum Height:	24.9 ft	7.6 m
Freeboard:	4.6 ft	1.4 m
Displacement:	50 lt	50 mt
Deadweight:	10 lt	10 mt
Clear Deck Space:	21 x 14 ft	6.5 x 4.4 m
Clear Deck Area:	270 ft ²	25 m ²
Deck Strength:	310 lb/ft²	1.5 t/m ²
Class Notations:	BUREAU VERITAS: I +HU AREA 3	ILL MACH CREWBOAT SEA

Capacities

Deck Cargo:	3.9 lt	4 t
Fuel Oil:	1,370 gal	5.2 m ³
Fresh Water:	65.8 gal	0.2 m ³





Pg.2 Further Specifications Pg.3 General Arrangement

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

ANNTOINETTE TIDE Further specifications



Machinery

Main Engines (2):	CAT C32		
Total HP:			2,600
Propellers (2):		Hamilton HM	521 Waterjets
Primary Generators (1):	20 kw	400 v	50 hz
Driven by:			CAT C2.2

Performance*

Fuel Consumption Vs Speed	
Maximum:	11.5 m³/day (130 gph) @ 30 knots
Cruising:	9.5 m³/day (100 gph) @ 25 knots
Economical:	8 m³/day (88.1 gph) @ 20 knots
Standby:	0.4 m³/day (4.4 gph) @ 0 knots
Range @ 30 Knots:	310 nm

Registration

Flag: LIBERIA	н	ome Port: MONROVIA
Hull Number: 532329		
Year Built: 2023		Call Sign: 5LQY4
Builder:		DAMEN SHIPYARDS
Tonnage (ITC):	62 GT	18 NT

Nav/Comms Equipment

Radar(s):	2
Depth Sounder:	1
Gyro Compass:	1
Radio:	2 x VHF; 1 x SSB

Accommodations

Passenger Seats:	42
Certified to Carry:	44

Special Equipment

Firefighting:	1x 600 m³/hr Fire Montior
Misc:	*Fuel and water shown for ship's use.; Jason's Cradle

Deck Equipment

Anchors (1):	21kg Fortress FX-85
Anchor Chain:	12.5 m of 13 mm chain per side

*Approximate values assuming Ideal Conditions


tdw.com

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

ANNTOINETTE TIDE

General Arrangement (Current configuration may vary.)





tdw.com

NOTICE: TH